



1. Tube Packing


1.1 Tube Quantity 20 pcs / Tube



1.2 Inner Box




1.3 Carton



1.4 Dimensions (Unit : mm)


	A	B	C
Tube	470±1.5	40.8±0.3	7.0±0.3
Box	490±5	205±5	90±5
Carton	510±5	215±5	220±5

1.5 Package




2. Box Packing

2.1 Box 500 pcs / Box




2.2 Carton



2.3 Dimensions (Unit : mm)

	A	B	C
Box	230±5	205±5	40±5
Carton	490±7	300±7	160±7

2.4 Package



Put in carton



3. Marking

Each reel shall be legibly marked with the following items.

PART NO.: GBU10K

DATE: 2023-05-18

PKG.: GBU

Q'TY: 0.5KPCS

RANGE: PASS




LOT. NO.: R21010108



Changzhou Galaxy Century Microelectronics Co., Ltd.

4. Type

Product code of taping shall be composed as indicated below.



5. Recommended storage condition

Storage period

Use the products within 12 months after delivered.

The first reflow soldering should be performed within 168 hours after opening the moisture-proof.

Storage conditions

Products should be stored in the warehouse on the following conditions.

Temperature : 0~ 35° C

Humidity : 30 to 70% relative humidity No rapid change on temperature and humidity

Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solderability.